

| Model | | JNS-4NVR-3P4 | JNS-8NVR-3P8 | JNS-16NVR-3P16 |
|----------------------------------|--------------------------------|---|----------------------------------|---|
| Video and audio input | Network video input | 4ch 4K POE IPC | 8ch 4K POE IPC | 16ch 4K POE IPC or 36ch 4K IPC |
| | Network access bandwidth video | 60M | | 216M |
| | Audio Input | IPC composite audio input | | |
| Smart Analysis | | Target Count, Object Left /Lost, Area Detection, Line Crossing | | Target Count, Object Left /Lost, Area Detection, Line Crossing, sound detection, fire detection, video diagnostic detection |
| Video and audio output | HDMI output | 1CH4K (3840×2160) /30Hz, 1920×1080/60Hz | | |
| | Audio Output | 1×RCA port | | |
| Video and audio codec parameters | Video Standard | H.265/H.264/MJPEG | | |
| | Video Resolution | 12M/8M/5M/3M/1080P/720P | | |
| | Encode Playback | Max support 4CH 1080P playback | 4/9/16ch playback simultaneously | |
| Recording Management | Video / Capture Way | Manual recording, timer recording, event recording, motion detection recording, alarm recording, motion detection recording/alarm recording, motion detection recording & alarm recording | | |
| | Playback Way | Time-phased playback, routine playback, event playback, external file playback, log playback | | |
| | Backup Way | Routine backup, event backup, record cutting backup | | |
| HDD | HDD Port | 2×SATA ports | 4×SATA ports | |
| | Max Capacity | Each port supports 6TB capacity | | |
| External Ports | Network Port | 1 RJ45 10M/100M10M/100self-adaptive | | |
| | USB Port | 3ports:1×USB2.0(front), 2×USB3.0(back) | | |
| | Serial Port | 1×RS-485 | | |
| | Alarm Input | 4ch alarm input, low electrical level effective, green connection line port | | |
| | Alarm Output | 1ch alarm output, Relay touch (1A@24VDC), NO, NC can program | | |
| POE | Ports | 4ports, 10M/100M Ethernet Ports for power | | |
| | Input Consumption | 52W | | |
| | POE Standard | IEEE802.3af | | |
| Network management | Network protocol | ONVIF (version 2.4 support), IPv4, UPnP (Plug and Play), NTP (Network Time Protocol), SADP (automatic search IP address), PPPoE (dial-up), DHCP (automatically obtain IP address), etc. | | |
| Others | WIFI | Extend 4G | | |
| | Power Supply | 48V 2A | 48V 3A | |
| | Power Consumption | < 10W (without HDD) | | |
| | Working Temperature | -10°C ~ +55°C | | |
| | Working Humidity | 10% ~ 90% | | |
| | Size | Equipment: 1.5U, 350mm (W) ×240mm (D) ×68mm (H) | Equipment: 440mm×356mm×68.5mm | |
| | | With package: 414mm×370mm×134mm | Packing: 460mm×135mm×560mm | |
| | Weight (without HDD) | N.W: 1.7Kg; with package: 2.9Kg | | N.W.: 5.7Kg; With packing: 6.9Kg |
| Installation Way | Desktop Installation | | | |